


Part number: **I30000009** Model: **SI30-AE15 NC**



Dimension in mm



1. TECHNICAL CHARACTERISTICS

Electrical data

Power supply type:	Alternating current
Working voltage:	[V] 20 ÷ 250
Protection class:	III

Outputs

Function:	NC
Max voltage drop:	[V] < 6
Max output current:	[mA] 300
Minimum output current:	[mA] 5
Max peak current:	[A] 1.5
Residual current:	[mA] < 1
Max switching frequency:	[Hz] 12

Detection zone

Switching distance-Sn:	[mm] 15
Real sensing distance-Sr:	[mm] 15 ±10%
Operative distance-So:	[mm] 0 ÷ 12.15

Accuracy and Deviations

Correction factor:	Stainless steel: 0.9 - Brass: 0.5 - Aluminium: 0.4 - Copper: 0.4
Hysteresis:	[%Sr] < 10
Switching point drift:	[%Sr] -1
Repeatability:	[%Sn] < 3

Environmental conditions

Temperature limits:	[°C] -25°C ÷ +70°C
IP rating:	IP65-IP66-IP67

Display and control elements

Display:	Output switching status - 1 x LED: Yellow
----------	---

Mechanical data

Housing:	Threded type
Thread designation:	M30x1.5
Dimensions: [mm]	M30x1.5 - L=84
Materials:	Housing: Nickel-plated brass - Sensing area: PC blue - Lock nuts: Nickel-plated brass
Mounting:	Not embeddable
Weigth: [g]	220

Electrical connection

Cable:	2 m - PVC/PVC - 2 x 0.50 mm ²
--------	--


Compliance to Standards / Directives

Directives compliance:	2014/30/EU -Electromagnetic compatibility directive (EMC) 2014/35/UE -Low voltage directive (LVD)
Standards compliance:	EN60947-5-2 - Product standard

2. NORME DI INSTALLAZIONE

WIRING DIAGRAM

2 WIRES CABLE



INSTRUCTIONS FOR CORRECT INSTALLATION

